MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Company: AccuStandard, Inc. Date MSDS Printed: 7/9/2007

125 Market Street Preparation Date: 7/3/2007

New Haven, CT 06513 Information Phone Number: 203-786-5290 Emergency Phone Number: 203-786-5290

Hours: Mon. to Fri. 8am-5pm

Catalog Number: C-140S-TP

Product Name: 2,2',3,4,4',6'-Hexachlorobiphenyl

Synonyms: N/A

Formula: N/A Molecular Weight: N/A

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

			ACGIH-TLV (mg/m3)		OSHA-PEL (mg/m3)	
Component(s) (2)	CAS#	Appr. %	TWA	STEL skin	TWA	STEL skin
2,2',3,4,4',6'-Hexachlorobiphenyl	59291-64-4	0.01				
Isooctane	540-84-1	99.99				

SECTION 3 - HAZARDS IDENTIFICATION

Symptoms of Exposure:

Irritating to eyes, skin, mucous membranes and upper respiratory system.

Inhalation may cause dizziness, nausea, lack of coordination, narcosis, unconsciousness. Ingestion may cause diarrhea, slight central nervous system depression, difficulty with breathing and fatigue.

Potential Health Effects:

Harmful if swallowed.

May be harmful if inhaled or absorbed through the skin.

Isooctane has produced kidney damage in rats in a subchronic oral laboratory study.

Routes of Entry:

Inhalation, ingestion or skin contact.

Carcinogenicity:

Notification of carcinogenic ingredients in quantity less than 0.1% is not required under Federal Hazard Communication Law.

Contains one or more components that are classified (ACGIH, IARC, NTP, OSHA) as a suspected cancer hazard in quantities less than 0.1%.

SECTION 4 - FIRST AID MEASURES

Emergency First Aid:

Get medical assistance for all cases of overexposure.

Skin contact: Wash thoroughly with soap and water. Get medical attention if irritation develops or persists.

Page 1 Preparation Date: 7/3/2007 Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: Do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:

Flash Point: 10.4 °F (-12 °C) (cc) Flammable Limits LEL (%): 1.00 Flammable Limits UEL (%): 6.00 Autoignition Temperature: 396 °C

Dangerous fire hazard.

Containers can build up pressure if exposed to heat.

Vapors can travel to a source of ignition and flash back.

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Extinguishing Media:

Use alcohol foam, carbon dioxide, dry chemical, or water spray when fighting fires involving this material.

Fire Fighting Procedures:

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Response:

Wear suitable protective equipment listed under Exposure Controls / Personal Protection. Eliminate any ignition sources until the area is determined to be free from explosion or fire hazards. Contain the release and eliminate its source, if this can be done without risk. Dispose as hazardous waste. Comply with Federal, State and local regulations.

SECTION 7 - HANDLING AND STORAGE

Store in a tighly closed container.

Store in a cool area away from ignition sources and oxidizers.

Electrically ground all equipment when handling this product.

Do not breathe vapor.

Do not get in eyes, on skin or clothing.

Avoid prolonged or repeated exposure.

This product should only by used by persons trained in the safe handling of hazardous chemicals.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls and Personal Protection Equipment (PPE):

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering and/or administrative controls should be implemented to reduce exposure.

Material must be handled or transferred in an approved fume hood or with equivalent ventilation.

Page 2

Catalog Number: C-140S-TP

Protective gloves must be worn to prevent skin contact.

(Nitrile or equivalent)

Safety glasses with side shields must be worn at all times.

General Hygiene Considerations:

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid

Odor: Mild odor

pH: N/A

Vapor Pressure: $41 \text{ mmHg } (21 \text{ }^{\circ}\text{C})$ Vapor Density (Air = 1): 3.9 g/l

Boiling Point: 99.2 °C Melting Point: -107.3 °C

Solubility in Water (%): Insoluble Specific Gravity ($H_2O=1$): 0.691 g/cm3 Flash Point: 10.4 °F (-12 °C) (cc) Explosion Limits (%): 1.00 to 6.00 Autoignition Temperature: 396 °C

Percent Volatile: 99+

Evaporation Rate (BuAc = 1): >1

Molecular Weight: N/A Molecular Formula: N/A

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: Heat; Contact with ignition sources

Materials To Avoid: Oxidizers

Hazardous Decomposition: Carbon oxidesHazardous Polymerization: Will not occur

SECTION 11 - TOXICOLOGICAL INFORMATION

See section 3 for specific toxicological information for the ingredients of this product.

SECTION 12 - ECOLOGICAL INFORMATION

By complying with sections 6 and 7 there will be no release to the environment.

Catalog Number: C-140S-TP

Page 3

Preparation Date: 7/3/2007

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

SECTION 14 - TRANSPORT INFORMATION

DOT UN Number: UN1262 Shipping Class: 3 Packing Group: II **FLAMMABLE**

SECTION 15 - REGULATORY INFORMATION

In addition to Federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

All components are listed on the TSCA Inventory.

WARNING: This product contains chemical(s) known to the state of California to cause cancer and to cause birth defects or other reproductive harm.

SECTION 16 - OTHER INFORMATION

This document has been designed to meet the requirements of OSHA, ANSI and CHIPs regulations.

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. It is intended for use only by persons having the necessary technical skill and at their own discretion and risk. Since conditions and manner of use are outside our control, we make

NO WARRANTY, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE.

Legend: N/A = Not Available ND = Not Determined NR = Not Regulated * * * End of Document * * *

Page 4

Alteration of any information contained herein without written permission from AccuStandard strictly prohibited. Preparation Date: 7/3/2007